

FVP10 Series

First Vocal Direct Thermal Printer



The unique voice feature that everyone's talking about...

FVP10 is the first operating POS printer to provide speech functionality with up to 255 voice commands. The audio can be streamed directly from the PC.

There is a default library of voice commands such as "Please take your receipt" or "Food order coming in" but more can easily be recorded in any language using STAR Sound Tool so that the printer is in fact multi-lingual!



There is an internal speaker with an audio jack for very noisy environments where external speakers may be necessary.

This feature makes it an invaluable tool for members of staff and customers alike.









Star-Asia Technology Ltd.

Tel: (852) 2799 6682 Fax: (852) 2798 5050 http://www.starasia.com email: info@starasia.com

▶ Front Loading

Unique front loading drawer style true "Drop-In & Print" paper loading. The square design, front operation and flat top provide a spacesaving opportunity as objects up to 7 Kgs can be placed on top of the printer without interfering with its operation.

With the shelf mount option, FVP10 can be discreetly mounted under a counter or sales desk providing a bigger counter space for operation.

Voice Function

Providing speech functionality with up to 255 voice commands. The audio can be streamed directly from the PC using STAR Sound Tool.

There is an internal speaker with an audio jack for very nosiy environments where external speakers may be necessary.

▶ High Quality & Reliability

High quality 203dpi output with high print speed of up to 250mm/s combined with fast, efficient throughput

(406 X 203 double density selectable)

Kitchen Printer

- **POS Printer**
- Hospitality Printer
- **Kiosk Printer**

FVP10 Specification	
Printing Method	Direct Thermal Line Printing
Printing Speed	Max 250mm/sec
Printing Resolution	203 x 203 dpi
Double density Graphics	406 x 203 dpi (selectable)
Print Case Design	Flat Top platform with splashproof downward
Paper	
Width	58 - 80mm (Adjustable by 1mm)
Thickness	0.065 - 0.15mm (65g -150g)
Roll Diameter	83mm
Top Margin	13mm (default) / 3mm (selectable)
Barcodes	1D Barcode X 9 sets, PDF417 & QR
Voice Function	Internal speaker & audio jack connector
Sound Storage	Up to 5 min plus sound management
	software - up to 255 voice commands
Logo Store	4Mbit Flash Rom
Character Set	ANK, BIG 5 & GB18030
Emulations	STAR Line mode & ESC/POS™
Interface	Built-in USB, optional Parallel, Serial or Ethernet
Dimensions (WXDXH)	144 X 227.7 X 114mm
Cutting Method	Full / Partial (Guillotine)
Reliability	
MCBF	60 millions lines
Print Head	150 km (recommended paper)
Cutter	up to 2 million cuts
Options	Counter Mounting Kit

Interface cable cover