

mC-Label3



Main Features

- » Easy maintenance design for long-term use, user can replace the consumable parts without any tools or professional skill
- » "One Touch Label" prints custom-made label by a single press on button
- » New paper loading design 【STAR patent】 can be operated with one hand, which has never been easier and more convenient
- » Up to 7 sensors for detecting paper exit, paper jam, label gap, black mark, paper end, cover open, paper position and paper width
- » IP22 waterproof & anti-insect design, linear adjustment paper width: 25.4~80mm
- » Multiple interfaces including Bluetooth (MCL32CBI model only), Ethernet x 1, USB-C (Power delivery) x 1, USB-A x 2 (peripheral), Wireless LAN (external Wifi adapter), Cash drawer port x 1
- » Provide SPOOLER API for managing the printing tasks and compatible with other STAR receipt printers by same control method
- » Support CloudPRNT cloud printing technology and WebPRNT web printing technology
- » Selectable cutting option: No-cut, Partial(a residual point at center) or Full Cut
- » Rich options: Wifi adapter, StarAsia M78 external Buzzer, SCD222U Customer Display, StarAsia BCR12D 1D barcode & 2D code scanner, CB2002/CD3336 cash drawer

mC-Label3 Series :

MCL32CBI USB + LAN + Bluetooth(Mfi)

MCL32CI USB + LAN

【Applicable Label】

- Strong Adhesive Sticky Paper ●
- Weak Adhesive Sticky Paper ●
- Die-Cut (Gap) Thermal Label ●
- Die-Cut (BM) Thermal Label ●
- Continuous Thermal Label ●
- Receipt ●




Applicable Label


Sticky Paper
(Strong or Weak
Adhesive)




Die Cut Label
(Gap)




Continuous
Thermal



Die Cut Label
(BM)



Receipt



mC-Label3

mC-Label3 Specification

Single hand Loading

STAR
Patent



User Swappable Consumable Parts



One Touch

prints custom-made label

Model	MCL32CBI USB + LAN + Bluetooth (Mfi) MCL32CI USB + LAN	
Case Color	Black	
Label Category	Sticky Paper (Strong or Weak Adhesive), Die Cut Thermal LABEL (Label gap or Black Mark), Continuous Thermal Label, Receipt	
Sensors	Paper Exit, Paper Jam, Label Gap or Black Mark, Paper End, Cover Open, Paper Position, Paper Width	
Installation	Horizontal	
Printing Method	Thermal Line	
Emulation	StarPRNT	
Printing Speed	Max. 180/mm	
Paper Specification	Type	Roll
	Paper Width	25.4 – 80 mm (linear adjustable)
	Roll Diameter	Max. φ102 mm
	Paper Thickness	49-150 um (depend on media)
	Top Margin	Min. 3 mm
Cutter	No Cut, Partial Cut or Full Cut	
Interface	<ul style="list-style-type: none"> • USB-C (Power delivery) x 1 • Bluetooth (MCL32CBI only) • LAN x 1 (WebPRNT / CloudPRNT) • Wifi (Add StarAsia external W i f i adapter) • USB-A x 2 • Cash Drawer x 1 	
Power	External 100 ~ 240V AC±10% (Power cord included)	
Dimensions	143 x 212 x 169 mm (W x D x H)	
Weight	Approximate 1.8 Kg (without paper roll)	
Inside the box	USB cable, LAN cable, power adapter, power cord	
Options	Wifi Adapter, M78 Alert Buzzer, CB2002/CD3336 Cash Drawer, SCD222U Customer Display, BCR12D Barcode Scanner	



Star-Asia Technology Ltd.

Tel: +852-2799 6682 Fax: +852-2798 5050

Unit 1906, Enterprise Square Two, 3 Sheung Yuet Road, Kowloon Bay, Hong Kong

"Star" is the trademark of "Star Micronics Co., Ltd."
All other trademarks, where used, are acknowledged.
All features and specifications are subject to change without notice.

star

www.StarAsia.com