80mm Kiosk Printer SK1 Series



- Fully opening paper cover
- Max 250mm/sec high speed printing
- Support label printing
- Sensor : Paper Empty, Paper Near-End, Black Mark & Label Gap
 Support 58/60/80/83mm paper width
- Paper core diameter 12/25.4mm changable
- Paper thickness from 59 to 150g
- Up to Φ120mm paper roll diameter
- Dual interface : USB + COM
- Compact and light weight
- Made in Japan

Optional Accessories



SPECIFICATION

Model

Printing Method

Emulation

Resolution

Number of dots

Printing / paper width

Paper Thickness

Printing Speed

Interface

Font

Barcode

2D Barcode

Cutter

Sensor

Power Supply

Reliability

Dimensions (WXDXH,mm)

Weight (g)

Safety Standard

SK1-311 series

SK1-V311 series

Direct line Thermal

StarPRNT™

8 dots/mm (203dpi)

432/448/576/640 dots

54/58mm, 56/60mm, 72/80mm, 80/83mm

59 ~ 150µm (W/O Presenter)

Max 250mm/sec

USB2.0 + RS232C (max. 115,200 bps)

8x16, 12X24 dots

JAN8/13, Code39/128, ITF, Codabar, UPC-A/E

QR, Maxicode, PDF417, DataMatrix

Partial or Full Cut (Command Control)

Paper Empty, Paper Near End, Black Mark, Label Gap

PS60A: 24VDC ± 5% /TYP 3A

Print Head: 150KM; Cutter: 2.0M Cut

127X145.5X85.4 *630* 127X85.4X182.3

725

CE, FCC, VCCI



Star-Asia Technology Ltd

T: +852-2799 6682 F: +852-2798 5050 Unit 1906, Enterprise Square Two, 3 Sheung Yuet Road, Kowloon, Hong Kong