STAR ASIA TSP143IVL

Enhance accuracy & efficiency From order To delivery





Direct Thermal linerless label printer with LAN, USB-C, USB-A, status diaplay, buzzer & optional wifi adapter

StarAsia TSP143IVL is an economical and compact thermal label printer to print sticky paper for takeaway & delivery orders and food labels in restaurants and grocery stores. Integrated with printer status display, chef can monitor the printer situation visually and application can alert new order by firing the speaker.

Key Feature

No liner, waste free

- 203dpi print resolution for high contrast text, graphics and barcodes
- ► Fast print speed up to 180mm/s
- Printer Status Diaplay & built-in speaker
- ► Applicable for 40mm, 58mm & 80mm label widths
- ▶ Up to 83mm roll diameter
- ► Up to 86µm label thickness
- Paper Taken Sensor for queuing labels
- LAN, USB-C, USB-A, optional WLAN
- Powered CloudPRNT for Cloud based software
- Powered WebPRNT for Web based software
- Internal power supply

Key Application



Kitchen orders, food & drink labelling



Grocery & Convenience stores








- Receipt Printer
 Label Printer
 Kiosk Printer
- Barcode Scanner Cash Drawer •
- Sticky Paper
 Thermal Label
- Genuine Ribbon Paper Roll •



Save paper with linerless media


Sticky Thermal Paper has no backing paper

Reduced Printing



Save up to 00%

Top Margin Reduction






No waste!!

StarAsia TSP143IVL can print variable length labels, meaning paper isn't wasted for labels or orders with just 1 or 2 line items. A top margin reduction of 5mm, a choice of label widths and vertical text reduction also reduce cost and environmental impact.

TSP143IVL Specification





Range of Connectivity Choices
■ Ethernet LAN
■ USB C
■ USB A (1.5A)
Cash Drawer
Optional WLAN
Windows Android Cash Drawer
LAN USB-C USB-A

Printer Model	TSP143IVL			
Technology	Direct Thermal Label Printer with IP22 splash resistant			
Printer Status Indicator	Display human readable printer status and integrated speaker			
Sensors	Taken sensor, Paper end sensor, Cover open sensor			
Print Speed	Max. 180 mm/second			
Resolution	203 dpi (8 dots/mm)			
Case Color	Black			
Paper Specifications	Туре	Thermal Sticky Paper Roll		
	Print Width	40mm/58mm/80mm (Paper Guide Provided)		
	Roll Diameter	Max. Ø 83mm		
	Thickness	65 ~ 98 μm		
Auto-Cutter	Partial cut (Leave center point)			
Connectivity	 USB-C x 1 Windows USB-A x1 (Andriod AOA / Peripherals connectivity) Ethernet x 1 (WebPRNT / CloudPRNT) Cash drawer port x 1 			
Emulation	StarPRNT			
Power Supply	Internal with Power Cable included 100 ~ 240V AC±10%			
Dimensions	140(W)x169(D)x123(D)mm (Printer), 45(W)x44(D)x22(D)mm (Indicator)			
Weight	Approx. 1.4 kg (without paper roll)			
Accessories Included in the box	Power Supply USB Cable	Paper Guide Lan Cable	Safety Guide Quick Setup Sheet	
Options	StarAsia Wifi Adapter StarAsia Cash Drawer (CB2002, CD3336, CD880) StarAsia Barcode Scanner (BCR12D, HCR12BT) Customer Display (SCD222U)			



Star-Asia Technology Ltd

T: +852-2799 6682 F: +852-2798 5050

unit 1906, Enterprise Square Two, 3 Sheung Yuet Road, Kowloon, Hong Kong